

Item	Datasheet	22KW
	Type	EST3L-32
	Picture	
Input	Power Supply	3P+N+PE
	Rated Voltage	AC400±10%
	Rated Current	32A(16A ,13A,10A adjustable)
Output	Output Voltage	AC400±10%
	Maximum Current	32A(16A ,13A,10A adjustable)
	Rated Power	22KW
User interface	Charger Connector	Cable
	Cable Length	5M
	Material	ABS +PC
	Led Display	three color LED /OLED(Optional)
	Start Mode	Plug in and charge, App(Optional),Card start(optional)
Safety	Ingress Protection	outshell IP65 / Socket IP54
	Impact Protection	/
	Electrical Protection	Over current protection
		Residual current protection
		Ground protection
		Surge protection
		Over/Under voltage protection
		Over temperature
	Certification	CE/ UKCA (Dekra)
	Certification Standard	EN IEC 61851,EN 62196
Environment	Installation	Wall mount
	Work Temperature	-20°C~50°C
	Work Humidity	3%~95%
	Work Altitude	<2000m
Package	Production Dimension(H*W*D)mm	320*193*105
	Package Dimension(L*W*H)mm	460*380*150
	Package Color	white
	Net/Gross Weight (kg)	5.01kg/6.01kg